

[Lead2pass New 400-201 Latest Dumps Free Download From Lead2pass (441-460)]

2017 November Cisco Official New Released 400-201 Dumps in Lead2pass.com! 100% Free Download! 100% Pass Guaranteed! 2017 latest released Cisco official 400-201 exam question free download from Lead2pass! All new updated questions and answers are real questions from Cisco Exam Center! Following questions and answers are all new published by Cisco Official Exam Center: <https://www.lead2pass.com/400-201.html>

QUESTION 441 What multicast protocols require RP? (Choose two) A. SMB. DMC. SSMD. BiDirE. anything like mLDPA. Answer: CD

QUESTION 442 What is a paradigm of segment routing? A. source routing Answer: A

QUESTION 443 Which are three characteristics of Cisco Embedded Packet Capture? A. It has the ability to preserve Ethernet encapsulation information when exported B. It has the ability to capture packets in the Cisco Express Forwarding path C. It uses EXEC-level commands to start and stop the capture D. The capture can be performed only on physical interfaces and sub-interfaces E. It has the facility to export the packet capture in pcap format F. The Cisco IOS output is displayed in a human-readable format Answer: BCE

QUESTION 444 Which two components does the LDP use to discover neighbors on a network segment? (Choose two) A. 224.0.0.1 multicast address B. 224.0.0.14 multicast address C. 711 udp port D. 224.0.0.2 multicast address E. 646 tcp port F. 711 tcp port G. 646 udp port Answer: DG

QUESTION 445 Which option is the Cisco cloud management platform that is designed for enterprise and public sector IT organizations to help build private and hybrid clouds? A. cisco intelligent automation for cloud B. cisco ucs director C. cisco cloud orchestrator D. cisco intercloud fabric Answer: A

Explanation: <http://blogs.cisco.com/datacenter/introducing-cisco-intelligent-automation-for-cloud-4-0>

QUESTION 446 Drag and Drop Question Drag and drop the QoS characteristics on the left onto its correct QoS mechanism on the right. Answer: QUESTION 447 Drag and Drop Question Answer: QUESTION 448 Which feature allows an MPLS TE Tunnel to be used by an IGP at the headend of the tunnel? A. MPLS TE link management B. MPLS TE autoroute announce C. generalized MPLS D. MPLS TE Forwarding Adjacency E. Differentiated Service TE Answer: B

QUESTION 449 Which statement about LDP session protection and ldp-igp sync is true? A. both LDP feature can't be used at the same time in MPLS LDP network B. ldp-igp sync re-exchanges label info when a down-up event occurs, keep the adjacency info in down-up event C. ldp session protection sync re-exchanges label info when a down-up event occurs, keep the adjacency info in down-up event D. both ldp feature must be used together to increase fast convergence on mpls ldp network Answer: D

QUESTION 450 Which option describes a service function as defined in SDN? A. a virtual server B. a virtual device C. a virtual chain D. a virtual network function Answer: D

QUESTION 451 Refer to exhibit. Customer reported internet stop working for a few times, and it occurred when ASBR1 router reloaded and ospf convergence faster than BGP. which command will solve the issue? A. graceful restart B. bfd min_rx 100 max_rx 100 multiplier 3 C. max-metric router lsa on startup 300 D. set overload bit on startup wait for bgp Answer: C

QUESTION 452 Which two characteristics of GMPLS are true? (Choose two) A. LMP can be used by the natively photonic switches network element type only B. The LSP is established directionally through only one signaling message C. The control channel can terminate on different node types that bearer channels span D. Two light paths traversing the same fiber link can share the same wavelength on that link E. OXCs manipulate wavelength that bear the label implicitly Answer: BE

QUESTION 453 Drag and Drop Question DND Multicast VPN, Arrange the steps on the left in order of how the P2MP TE traffic is forwarded across the network. Answer: QUESTION 454 What are the improvements in SNMPv3 regarding security? A. authentication and privacy B. its administration offers logical contexts C. view-based access control D. remote configuration. Answer: ABCD

QUESTION 455 Specify the label modes for rsvp-te. A. - control method (like ordered or independent) B. - distribution mode (like downstream on demand or unsolicited) C. - retention mode (like conservative or liberal) Answer: ABC

QUESTION 456 A service provider engineer enabled the BGP next-hop tracking feature and also turned the OSPF to increase the network convergence in case of network failures. However, the operator engineer notices that in case of PE failure, the network convergence is still slow. Which configuration must the operator use to remedy this failure scenario? A. router ospf 1 no default-information originate timer throttle lsa all 1 5 5000 timer throttle spf 1 5 5000 B. router bgp 65000 address-family ipv4 no bgp nexthop trigger enable bgp additional-paths install! address-family vpnv4 no bgp nexthop trigger enable bgp additional-paths install C. router bgp 65000 address-family ipv4 bgp nexthop trigger delay 1! address-family vpnv4 bgp nexthop trigger delay 1 D. router ospf 1 default-information originate always metric-type 1 timer throttle lsa 1 5 5000 timer throttle spf 1 5 5000 E. ip prefix-list PREFIX_32 permit 0.0.0.0/0 ge 32! route-map ONLY_32 permit 10 match ip address prefix-list PREFIX_32 match source-protocol ospf! router bgp 65000 address-family vpnv4 bgp nexthop route-map ONLY_32 Answer: C

QUESTION 457 There was also another question for which the answer was prefix prioritization. A. prefix prioritization. Answer: A

QUESTION 458 A Corporate_ABC located in the US acquired Company_XYZ, which is located in Europe. Both companies are connected to the internet using their local ISP. A management VLAN must be built

using subnet 192.168.1.0/24 across the ABC and XYZ. Which solution meets this requirement? A. VPLSB. AToMC. Layer 3 VPND. L2TPv3 Answer: D QUESTION 459 In a L2VPN service, customer CE1 sends frames to PE1 using a CoS marking value of 3. However, the remote CE2 receives those frames from PE2 with a CoS marking value of 0. Which description of this behavior is true? A. Egress PE2 is not configured with an outbound policy-map facing CE2 to preserve the customer CoS markingB. Egress PE2 is not configured with mpls ldp explicit-null commandC. Ingress PE1 is remarking the CoS frame received from CE1 with value of 0.D. Egress PE2 is marking EXP 0 upon label imposition. Answer: C QUESTION 460 The service provider has the following VPLS requirements. A PE must learn dynamically remote PEs that are members of the same VPLS domain. The VPLS signaling must be in a point-to-multipoint fashion way according to RFC 4761 (Kompella). Which feature must be enabled to meet these requirements? A. LDP signalingB. BGP signalingC. RSVP signalingD. RSVP auto discoveryE. LDP auto discovery Answer: B Explanation: RFC 4761 Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling Lead2pass offers the latest Cisco 400-201 exam questions and answers in PDF & VCE. We promise 100% 400-201 exam pass or full money back (Have a try- If success, you will get a high pay job! Failed, nothing, money back!)! We provide instant download of our 400-201 dumps after payment so you can study earlier than others! 400-201 new questions on Google Drive: <https://drive.google.com/open?id=0B3Syig5i8gpDMExNMWJIYTIIcUU> 2017 Cisco 400-201 exam dumps (All 647 Q&As) from Lead2pass: <https://www.lead2pass.com/400-201.html> [100% Exam Pass Guaranteed]